




FIRECO LIGHTWEIGHT “ENTRY” TELESCOPIC MAST Ø66mm WITH INTERNAL CABLE

	Part Number	Extended Height (m)	Retracted Height (m)	Max Head Load (kg)	Weight (kg)	Max Wind Speed (Km/h)	Max surface area (m ²)
2 section	CN.5211	2.004	1.200	23	4.5	180	0.24
	CN.5212	2.494	1.450	23	5.0	165	0.24
	CN.5213	2.990	1.700	23	5.5	150	0.24
3 section	CN.5301	2.498	1.135	20	5.5	150	0.2
	CN.5302	3.003	1.300	20	6.0	135	0.2
	CN.5303	3.443	1.470	19	6.5	120	0.2
	CN.5304	3.969	1.640	18	8.5	110	0.2
4 section	CN.5406	2.500	1.050				
	CN.5407	3.000	1.225				
	CN.5408	3.500	1.350				
	CN.5409	4.000	1.475				

CN.5211.PB indicates mast without hand pump, CN.5211.HB indicates mast with hand pump

CN.5211.PB indicates Cable 4 x 1.5mm², CN.5211.PH 5 x 1mm² + 4 x 0.5mm²

Options & Accessories

			
Lower External Mounting Bracket BK.30101	Upper External Mounting Bracket BK.30201	Round Roof Mounting Bracket BK.30002	Square Roof Mounting Bracket BK.30052
			
24mm Security Pin with M10 Tapped Hole to suit Mast Head. 11169/1	Sand Scraper Rings Example: CA.5221.H_RAS	Tripod Leg Length 0.850m (Suitable for masts 0-6.9m) TP.35301	Tripod Leg Length 1.100m (Suitable for masts 7-9.9m) TP.35302