








FIRECO LIGHTWEIGHT “SUPER ENTRY” TELESCOPIC MAST Ø80mm WITH INTERNAL CABLE

	Part Number	Extended Height (m)	Retracted Height (m)	Max Head Load (kg)	Weight (kg)	Max Wind Speed (Km/h)	Max surface area (m ²)
2 section	CO.5221	2.000	1.185	30	6.0	155	0.5
	CO.5222	2.470	1.435	30	6.5	140	0.5
	CO.5223	2.960	1.685	30	7.0	130	0.5
3 section	CO.5311	2.473	1.120	28	7.0	135	0.4
	CO.5312	3.004	1.287	28	7.5	120	0.4
	CO.5313	3.473	1.480	28	8.0	110	0.4
	CO.5314	3.964	1.647	28	8.5	100	0.4
4 section	CO.5436	3.499	1.240	26	8.5	115	0.3
	CO.5437	3.909	1.380	25	9.0	105	0.3
	CO.5438	4.499	1.535	24	9.5	95	0.3
	CO.5439	4.939	1.675	23	10.0	90	0.3
5 section	CO.5511	4.000	1.266	22	9.5	115	0.2
	CO.5512	4.448	1.374	22	10.0	105	0.2
	CO.5513	5.000	1.498	21	10.5	95	0.2
	CO.5514	5.500	1.606	21	11.0	90	0.2
	CO.5515	6.000	1.714	20	11.5	85	0.2
	CO.5516	8.000	2.200				
6 section	CO.5609	4.000	1.176				
	CO.5610	4.500	1.292				
	CO.5611	5.000	1.420				
	CO.5612	5.500	1.527				
	CO.5614	8.000	2.060				
	CO.5614	8.000	2.060				

CO.5221.**PB** indicates mast without hand pump, CO.5221.**HB** indicates mast with hand pump

CO.5221.**PB** indicates Cable 4 x 1.5mm², CO.5221.**PH** 5 x 1mm² + 4 x 0.5mm²

Options & Accessories

			
<p>Lower External Mounting Bracket BK.30105</p>	<p>Upper External Mounting Bracket BK.30205</p>	<p>Round Roof Mounting Bracket BK.30005</p>	
			
<p>24mm Security Pin with M10 Tapped Hole to suit Mast Head. 11169/1</p>	<p>Sand Scraper Rings Example: CO.5425.H_RAS</p>	<p>Square Roof Mounting Bracket BK.30051</p>	
			
<p>Tripod Leg Length 0.850m (Suitable for masts 0-6.9m) TP.35306</p>	<p>Tripod Leg Length 1.100m (Suitable for masts 7-9.9m) TP.35307</p>	<p>Tripod Leg Length 1.500m (Suitable for masts 10-14.9m) TP.35308</p>	<p>Tripod Leg Length 2.000m (Suitable for masts above 15m) TP.35309</p>